

बीरबल साहनी पुरावनस्पतिविज्ञान संस्थान, लखनऊ
BIRBAL SAHNI INSTITUTE OF PALAEOBOTANY, LUCKNOW

टेलीग्राम पेलियोबॉटनी

दूरभाष 2740008, 2740011

फैक्स ९१-91-522-2740485, 2740098

बी सा पु सं /III/भंडार एवं क्रय/ C-1678

53, विश्व विद्यालय मार्ग

लखनऊ - 226007

Date: 03.03.2015

Speed Post

Convener, Website Committee
BSIP, Lucknow

- pH/ Conductivity/ TDS/ORP/Salinity and temp meter
 - Water proof Dissolved oxygen meter
 - Water proof fluoride meter
- (Details attached)

Subject: -----


Dear Sirs,

This Institute intend to purchase item mentioned above. Sealed quotations are invited so as to reach this office on or before 5:00P.M. on 16.03.2015 duly superscribed by "ph/Water Dissolved oxygen/ fluoride meter" due to open in presence of vendors at a later date to be notified.

While submitting quotation please note that:

- The material may either of indigenous manufacturer or of foreign make, available from ready stock. Any offer to supply on forward Delivery Basis under suppliers own quota license will also be considered.
- The price quoted should be F.O.R. Destination.
- Your rates should include packing, insurance and forwarding charges.
- The rates of Sales Tax should be clearly indicated wherever chargeable. The tendered should also indicate Central/Sales Tax Registration Number and date in this quotation.
- Specific mention should be made whether the offer is for supplies available ex-stock. In case the officer is on Forward Delivery basis, firm delivery period must be indicated.
- The cover should be sealed and superscribed "Quotation for "ph/Water Dissolved oxygen/ fluoride meter" must be written on envelope in the name of "Director, Birbal Sahni Institute of Palaeobotany, Lucknow". The quotations not complying the procedure will be rejected.
- Payments will be made by crossed cheque on The Indian Overseas Bank, Lucknow only after receipt and acceptance of supply and installation/ if required satisfactory.
- The acceptance of the quotation will rest with the Director who does not bind himself to accept the lowest quotation and reserves the right to himself to reject or partially accept any or all the quotation received without assigning any reasons.
- The quotations are liable to be cancelled if any of the above mentioned conditions are not complied with.

Yours sincerely,


(Ram Shukla)
Registrar

Technical specifications

• pH/Conductivity/TDS/ORP/Salinity and Temp meter

Specifications	Range	Resolution	Accuracy
pH	0.01 to 14.00pH	0.01pH	±0.02pH
Conductivity	10 to 19,990μS	0.1μS	±2%FS
TDS	10 to 19,990ppm (mg/L)	0.1ppm	±2%FS
ORP	-1500mV to 1500mV	1mV	±3mV
Salinity	0 to 10.00ppt	0.01ppt	±2%FS
Temperature	32.0°F to 194.0°F (0.0°C to 90.0°C)	0.1°	±2°F/1°C

Dimensions 3.7 x 4.2 x 2" (96 x 108 x 45mm)

Weight 12oz (340g)

4) Water proof Dissolved oxygen meter

Specifications	Range	Max Resolution	Accuracy
DO (saturation mode)	0 to 200.0%	0.1%	±2% FS
DO (concentration mode)	0 to 20.00ppm (mg/L)	0.01ppm (mg/L)	0.4ppm (mg/L)
Temperature	32 to 122°F (0 to 50°C)	0.1°F/°C	±1.8°F (1°C)
Dimensions	1.4x6.9x1.6" (36x176x41mm)		
Weight	3.8oz (110g)		

5) Water proof fluoride meter

Specifications	Range Max.	Resolution	Accuracy
ppm	0.1 to 10ppm	0.1ppm	±3% rdg
Temperature	32 to 140°F (0 to 60°C)	0.1°F/°C	±1.8°F/1°C
Dimensions	1.4x6.8x1.6" (36x173x41mm)		
Weight	7.4oz (210g)		